



MLR-352H-PE

MLR

Climate Chambers

294 L

Versatile Climate Chambers

MLR Climate Chambers are suitable for a wide range of applications, including plant growth and insect studies. The wide variety of temperatures, humidity and lighting patterns that are essential in research, environmental studies and testing can be accurately reproduced and controlled.

Accurate Control


Microprocessor P.I.D and Refrigeration Capacity Control eliminate temperature fluctuations improving temperature control. The small and light weight membrane-type humidity sensor allows for high accuracy and reproducibility.

Wide Variety Programming

Temperature and light settings are programmable to provide the perfect cycles for vernalization. 10 programmes of up to 12 steps each can be memorized.

Ease of Use

Data can be viewed on the LCD control panel display and can be automatically stored for approximately 2 weeks (at 6 minute intervals). Temperature and humidity can be calibrated easily from the control panel.




Optimum Repeatability

Superior precision and repeatability offer the optimum environments for various experiments as well as energy and electricity savings.



Variable Applications

Create the optimum environments for various applications such as research and testing of a number of different plants and insects.



Intuitive Usability

Graphic LCD panel with pop-up menu function on control panel provides more visual display and allows intuitive operation.

MLR Climate Chambers




Microprocessor Control

Microprocessor P.I.D control of temperature and humidity (0°C to +50°C, 0 to 20,000lux and 55 to 90%RH resp.) create the optimum environments for various applications.

Programmable Settings

The temperature and light settings are programmable to provide the perfect cycles for vernalization. The unit allows the programming of starting day and time of operation and 10 programmes of up to 12 steps each to be memorized. Switch between the selectable clock mode or timer mode and use of the Join Mode for allowing multiple programs to be linked.

Unit: mm (inch)



Model Number	MLR-352-PE	MLR-352H-PE
External Dimensions (W × D × H)	mm	760 × 700 × 1835
Internal Dimensions (W × D × H)	mm	520 × 490 × 1135
Volume	liters	294
Net Weight	kg	226
Performance		
Temperature Control Range & Fluctuation	°C	0 ~ +50 (lamp off) ±0.3 +10 ~ +50 (lamp on) ±0.3
Temperature Uniformity	°C	±1 (lamp off) ±2.5 (lamp on)
Humidity Level & Fluctuation	%RH	N/A
Light control range		60-90 / LS:0 (15-45°C) 55-85 / Lamp On (15-45°C)
		Programmable 0 ~ 20000
Control		
Temperature Sensor		Thermistor
Display		LCD
Refrigeration		
Refrigerant*		R-513A
Refrigerant weight	g	270
Refrigerant GWP		631
Total Refrigerant weight (CO ₂ equivalent)	t	0,170
Construction		
Exterior Material		Painted Steel
Interior Material		SS SUS-304
Insulation Material		PUF
Outer Door	qty	3
Outer Door Lock		N
Field Reversible Door		N/A
Inner Door	qty	1
Shelves	qty	5
Shelf Dimensions (W × D × H)	mm	
Max. Load per Shelf	kg	25
Access Port	qty	1
Access Port Position		Ceiling
Access Port Diameter	∅ mm	40
Alarms (R = Remote Alarm, V = Visual Alarm, B = Buzzer Alarm)		
Power Failure		R
Out of Temperature Setting		B-R
High Temperature		B-R
Out of Humidity Setting		N/A
Door open		V-B
Electrical and Noise Level		
Power Supply	V	230
Frequency	Hz	50
Noise Level ¹⁾	dB	47 dB (light ON) / 45 dB (Light OFF)

Appearance and specifications are subject to change without notice.

¹⁾ Nominal value
* Complies with Art. 11, Annex III of F-Gas Regulation (EU) No 517/2014. Contains fluorinated greenhouse gases.

PHC Europe

A Member of PHC Group

Eikdonk 1 | 4825 AZ Breda | Netherlands
T: +31 (0) 76 543 3833

www.phcd.com/eu/biomedical